

## Product data sheet

### Characteristics

# ML2031RCD10-WE

## CLIPSAL RCD - 2P - 10mA - 20A - 250V



### Main

Product or component type	Residual current device
Product brand	Clipsal
Poles description	2P
[In] rated current	20 A
Earth-leakage sensitivity	10 mA

### Complementary

[Ue] rated operational voltage	250 V AC
Size	116 x 76 mm conforming to DIN 43880
Colour	White electric

### Environment




Standards	AS/NZS 3190
-----------	-------------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	176.0 g
Package 1 Height	7 cm
Package 1 width	9.1 cm
Package 1 Length	11.7 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Weight	0.996 kg
Package 2 Height	12 cm
Package 2 width	9.1 cm
Package 2 Length	36 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Weight	9.96 kg
Package 3 Height	36 cm
Package 3 width	34.5 cm
Package 3 Length	40.5 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>