


64685043-10 | 6468 5 043-10



LSA-PLUS® Disconnection Module, cat 3, 2/10, PROFIL mounting

Product Classification

Regional Availability	Australia/New Zealand
Product Type	Disconnection module
Product Brand	LSA-PLUS®
Product Series	LSA-PLUS

General Specifications

ANSI/TIA Category	3
Color	White
Mounting	PROFIL rods
Pairs, quantity	10
Termination Punchdowns, minimum	200 times
Termination Tool	LSA-PLUS Punchdown tool
Termination Type	IDC

Electrical Specifications

Contact Resistance, maximum	3 mOhm
Current Rating, maximum	2 A
Dielectric Strength	2 kV
Insulation Resistance, minimum	50 GOhm

Material Specifications

Contact Base Material	Brass
Contact Plating Material	Silver
Material Type	Polybutylene terephthalate (PBT)

Environmental Specifications

Operating Temperature	-5 °C to +60 °C (+23 °F to +140 °F)
Relative Humidity	Up to 95%, non-condensing
Environmental Space	Indoor Outdoor
Flammability Rating	UL 94 V-0

Packaging and Weights

Packaging quantity	10
Packaging Type	Box Carton

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant

