



## GLIDER-SM

CLEVERTRONICS Glider Blade Exit, Surface Mount, Trade Series, Picto All, Double Sided



### PRODUCT INFORMATION

|                          |                                                                         |
|--------------------------|-------------------------------------------------------------------------|
| Part Number              | GLIDER-SM                                                               |
| MIC                      | AUA03510130001                                                          |
| Description              | Glider Blade Exit, Surface Mount, Trade Series, Picto All, Double Sided |
| Construction             | PC/ABS body with PC diffuser                                            |
| Mounting                 | Surface Mount, Double Sided                                             |
| Dimensions L x W x H     | 341mm x 60mm x 215mm                                                    |
| Weight                   | 1.80kg                                                                  |
| Operating Mode           | Maintained                                                              |
| Testing System           | N/A - Manual test switch                                                |
| Battery                  | Lithium Iron Phosphate, 3.2V 1100mAh                                    |
| Charging Method          | Intelligent Current Limited Constant Voltage                            |
| Diffuser                 | All pictograph directional inserts included in the box                  |
| Lamp/s                   | 12 x Samsung LED, 100,000 hours                                         |
| Operating Voltage        | 240V AC; 50Hz                                                           |
| Power Consumption        | 1.3 Watts (Standby), 2.6 Watts (Max)                                    |
| Earth Leakage            | 0.42                                                                    |
| IP Rating                | IP20                                                                    |
| Operating Temperature    | 1°C to 40°C                                                             |
| AS2293 Classification    | C0=E4, C90=E4, C180=E2.5, C270=E3.2                                     |
| Viewing Distance         | 24m                                                                     |
| Applicable Standards     | AS/NZS3820, CISPR15, AS/NZS2293.3                                       |
| Compliance Marking (RCM) |                                                                         |

### REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION      |
|-------------|------------------|
| 1560180     | Battery          |
| 8003552     | Emergency Driver |
| 8012080     | LED Board        |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.