

Product datasheet

Specifications



EVlink Wallbox - 22 kW - T2 socket outlet with shutter - charging station

EVH2S22P04K

! To be discontinued

! To be discontinued on: 30 Dec 2023

! To be end-of-service on: 31 Dec 2025

Main

Range	EVlink
Product Name	EVlink Wallbox
Product Or Component Type	Charging station
Device Short Name	EVH2
Poles Description	3P + N
Mounting Mode	Wall-mounted
Offer Type	Standard
Max Power	22 kW 32 A
Number Of Charge Point	1
Connection To The Vehicle	Socket-outlet T2 with shutter
Access Control System	Key

Complementary

Rated Supply Voltage	380...415 V AC 50/60 Hz
Earthing System	TT TN
Number Of Inputs	1
Input Type	Contact for power limitation Contact for delayed charging
Control Type	1 white button, function: stop/restart Green button, function: cable unlocking
Local Signalling	1 multi-colour LED, function: status indication
Height	480 mm
Width	331.5 mm
Depth	170 mm
Net Weight	5.6 kg
Colour	White (RAL 9003) Grey (RAL 7016)
Standards	IEC 62196-2 IEC 62196-1 IEC 61851-1 IEC 61851-22

Product Certifications	CB CE
------------------------	----------

Environment

Ip Degree Of Protection	IP54 conforming to IEC 60529
-------------------------	------------------------------

Ik Degree Of Protection	IK10 conforming to IEC 62262
-------------------------	------------------------------

Ambient Air Temperature For Operation	-30...50 °C
---------------------------------------	-------------

Ambient Air Temperature For Storage	-40...80 °C
-------------------------------------	-------------

Relative Humidity	5...95 %
-------------------	----------

Packing Units

Unit Type Of Package 1	PCE
------------------------	-----

Number Of Units In Package 1	1
------------------------------	---

Package 1 Height	26.000 cm
------------------	-----------

Package 1 Width	40.000 cm
-----------------	-----------

Package 1 Length	53.500 cm
------------------	-----------

Package 1 Weight	8.120 kg
------------------	----------

Unit Type Of Package 2	P06
------------------------	-----

Number Of Units In Package 2	4
------------------------------	---

Package 2 Height	50.000 cm
------------------	-----------

Package 2 Width	60.000 cm
-----------------	-----------

Package 2 Length	80.000 cm
------------------	-----------

Package 2 Weight	41.940 kg
------------------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)