

Product Line: Stanilite®
Product Group: Excel LED Exit Range
Additional Description: LED Quickfit Exit



Catalogue No.	Description
PQFLED	LED Quickfit Exit
PQFNXSLED	LED Quickfit Nexus LX Exit
PQFNRFLED	LED Quickfit Nexus RF Exit

Features:

- Architecturally pleasing slim line design
- Unique steel Quickfit® mounting bracket that provides strength and enables quick and easy maintenance
- PerpetuLED® LED technology 100,000 hours plus lamp life
- Includes all pictograph diffuser options for single or double sided installation
- Advanced PulseTIME® dual rate battery charger with high temperature NiCad batteries
- Universal wall/ceiling mounting, can also be rod or wire suspended
- Option - Standard, Nexus® LX monitored or Nexus RF monitored
- Retrofit capability; fits into any existing Quickfit mounting bracket
- Frame only available for upgrade of installed product (less mounting bracket and diffusers) - will accept existing diffusers

Dimensions:

Length	Width	Height (Including Bracket)
379mm	72mm	214mm

Weight:

Model	Weight
All Models	1.8kg

Construction:

Part	Construction
Body	UVFR ABS Body
Diffuser	Opal Acrylic
Bracket	White Powder Coated Zinc Steel

Light Source:

Model	Light Source
All Models	Multiple LED 1.6W

Power Consumption:

Model	Power Consumption
Standard	3.6W
Nexus LX	3.9W
Nexus RF	3.9W

Photometrics:

Model	Class	Classification
All Models	C0	D3.2
	C90	D3.2

Spare Parts:

Catalogue No.	Description
03-01218	Battery 4 Cell Sub-C NiCad Straight 4.8V 1.8Ah

Accessories:

Catalogue No.	Description
MQFCL	Cantilever Bracket
QFWGCM	Wire Guard - Ceiling
QFWGWM	Wire Guard - Wall

Thomas & Betts emergency lighting products are designed to comply with AS2293 and meet relevant Australian EMC Standards. Due to ongoing product development, specification changes may result.